





# PERFORMANCE DATA SHEET

#### MANUFACTURER

Name: ATLAS FILTRI SRL Address: Via Pierobon 32 - Limena, 35010, PD Phone: +39 049769055

## PRODUCTS

- BIG F PRO 156
- BIG F PRO 256
- BIG F PRO 267

## SUBSTANCES REDUCTION

SELLER Name: Atlas FILTRI SRL distributors



The Atlas Filtri models listed above have been tested and certified under AS/NZS 4020 and AS/NZS 3497 and relevant NSF Standard listed in Clause 1.2 for reduction of Sediment. The performance of these products has been verified and substantiated as the test data summarized below indicates. These substances may not be in your water.

class IV	TREATMENT TYPE Turbidity and particulate removal		PLAIN LANGUAGE DESCRIPTION Reduce Cloudiness		CONFORMANCE TO NSF STANDARDS AND PROTOCOLS NSF 42		
SUBSTANC	E NHMRC ADWG or USEPA SDWA MCL	AVERAG INFLUENT	MAXIMUM EFFLUENT	MINIMUM PERCENT REMOVAL	AVERAGE EFFLUENT	AVERAGE PERCENT REMOVAL	
Sedime		16638	515	> 98.01%	269	> 98.2%	
<ul> <li>MCL - Maximum Contaminant level</li> <li>Mg/I - milligrams per litre</li> <li>Testing conditions:</li> <li>Flow rate was controlled at 24 gpm</li> <li>pH 7,8 +/- 0,05</li> <li>Temperature 21 +/- 3 degree C</li> </ul>			warranty ir handling a conditions.	nformation and to a nd installation. Per	for more specific pro avoid contamination formance will vary o educed by this proc	from improper on local water	

## USE GUIDELINE

- Minimum Operating pressure 50 kPa
- Maximum operating pressure 1205 kPa
- Do not Allow exposure to temperature below 4°C
- Maximum operating temperature 45°C
- Nominal Flow rate

MODEL	FLOW-RATE
DP BIG 156	54 L/min
DP BIG 256	70 L/min
<b>DP BIG 267</b>	95 L/min

· This system has to installed according to local plumbing codes on the cold water line

Replacement cartridges

MODEL	CARTRIDGE
DP BIG 156	TS 10 BIG - CPP 10 BIG (CBEC 10 BIG)
DP BIG 256	TS 20 BIG - CPP 20 BIG (CBEC 20 BIG)
DP BIG 267	TS 20 BIG - CPP 20 BIG (CBEC 20 BIG)

• This system requires regular replacement of the filter cartridge to maintain proper operation. Varying Sediment or organic substances levels may affect replacement frequency.

• Be sure to change the filter cartridge at least every six months; Or whenever you detect a change in taste or odour or decrease in flow.



**CAUTION** - Do not use with water that is microbiologically unsafe or of unknow quality without adequate disinfection before or after the system. This System may be used on disinfected water that may contain filterable cyst.

Date: 27/10/2020

Manufacturer's Signature



- les











ATLAS FILTRI S.r.I. | via Pierobon, 32 | 35010 Limena, Italy Tel. +39.049.76.90.55 | Fax +39.049.76.99.94 | www.atlasfiltri.com