TM aleArr

melt-blown polypropylene and ScaleArmor[™] media

Cartridges combining a pre-filter element made from melt-blown polypropylene with ScaleArmor[™] media for anti-scale water conditioning. CPP ScaleArmor[™] cartridges provide fine sediment pre-filtration at 5 micron and anti-scale and anti-corrosion treatment with proven effectiveness that removes with time old calcareous incrustations and offers a corrosion protection for boilers, pipes, pumps and appliances. CPP ScaleArmor[™] cartridges are available in 10" and 20" heights, standard and BIG (4,5" OD)



MAX WORKING TEMPERATURE 45°C (113°F) MIN WORKING TEMPERATURE 4°C (39,2°F)

COLDWATER

MAX TOTAL HARDNESS

50°f (500 ppm CaCO₂) Remark - the treated water can be heated up to 75°C - 80°C. above that temperature the ScaleArmor[™] media loses gradually its effectiveness.

Sediment filtration, anti-scale and anti-corrosion conditioning. Max life-span: 6 months. Maintenance: none.

SPECIFICATIONS

Selected raw materials, suitable for drinking water. Filter medium: polypropylene. End caps: polyethylene. Treatment material: ScaleArmor[™] certified media





CPP ScaleArmor[™]

MELT-BLOWN POLYPROPYLENE AND ScaleArmor[™] MEDIA - CARTRIDGES WITH DOUBLE OPEN END (DOE)

| PART NUMBER | MODEL | NOMINAL HEIGHT | NOMINAL FILTRATION mcr | MAX FLOW RATE I/h | DIMI A | ENSIONS B | mm C |
|----------------|--------------------------------|-------------------|---------------------------|----------------------|-----------|--------------|---------|
| RA5765508 | CPP 10 ScaleArmor [™] | 10" | 5 | 1300 | 250 | 61 | 28 |
| RA5767508 | CPP 20 ScaleArmor [™] | 20" | 5 | 1600 | 505 | 61 | 28 |



CPP BIG ScaleArmor[™]

MELT-BLOWN POLYPROPYLENE AND ScaleArmor[™] MEDIA - CARTRIDGES WITH DOUBLE OPEN END (DOE)

| PART | | NOMINAL | NOMINAL | MAX | DIMENSIONS mm | | |
|-----------|------------------------------------|---------|----------------|---------------|---------------|-----|----|
| NUMBER | MODEL | HEIGHT | FILTRATION mcr | FLOW RATE I/h | | | |
| RA5765608 | CPP 10 BIG ScaleArmor [™] | 10" | 5 | 2500 | 250 | 112 | 28 |
| RA5767608 | CPP 20 BIG ScaleArmor [™] | 20" | 5 | 4000 | 511 | 112 | 28 |

CONFIGURATIONS:

- SX standard configuration double open end (DOE).

MODELS:

- CPP ScaleArmor[™] series 10 and 20", OD 2.40" and 4.50", ID 1.10", SX configurations.

CERTIFICATIONS:





improving www.atlasfiltri.com | MADE IN ITALY



Scale Armor[™] media is certified by IAPMO R&T against IAPMO Z601 for material safety requirement.