



DOSAPLUS [new]

THE EVOLUTION
CONTINUES!



THE RANGE
IS ENHANCED
WITH NEW MODELS
AND VARIANTS

**DESCALING DOSING
SYSTEM FOR ALL NEEDS!**



DISCOVER THE NEW MODELS...



21 2P FF

DOSAPLUS 21 2P FF DOSAPLUS 22 3P FF

- Brass head
- Rotational female brass unit
- Adjustment screw for correct dosing
- DOSAPLUS 21 - 2 piece (head, cup)
- DOSAPLUS 22 - 3 piece (head, ring, cup)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head Dosapulus 21: CW 602 N brass.
 Head and ring nut Dosapulus 22: CW 602 N brass.
 Bowl: SAN.
 O-ring: EPDM.
 Breather-valve: body stainless steel, o-ring EPDM.
 Bellow: rubber (NBR).
 IN/OUT threads: CW 614 N brass, 1/2" BSP



22 3P FF



DOSAPLUS 23 FF with bypass DOSAPLUS 24 FF

- Plastic head -
- Rotational female brass unit -
- 2 pieces (head, cup) -
- Dosapulus 23 with by-pass -
- to facilitate maintenance operations

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head: reinforced polypropylene.
 Brass rotational connection group: CW 602 N brass.
 Bowl: SAN.
 O-ring: EPDM.
 Breather-valve: body stainless steel, o-ring EPDM.
 Bellow: rubber (NBR).
 IN/OUT threads: CW 614 N brass, 1/2" BSP



23 FF bypass



24 FF



1 2P DG

DOSAPLUS 1 2P DG

- Brass head
- Rotational female brass unit with rotating nuts
- Adjustment screw for correct dosing
- 2 pieces (head, cup)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head: CW 602 N brass.
 Bowl: SAN.
 O-ring: EPDM.
 Breather-valve: body stainless steel, o-ring EPDM.
 Bellow: rubber (NBR).
 IN/OUT threads: CW 614 N brass, 1/2" BSP

ALWAYS
~~IMPOSSIBLE~~
 INSTALLATIONS!

DOSAPLUS 21 TA 2P FF
DOSAPLUS 1 TA 2P DG

The new elongated head Dosaplus (DIMA version) are the ultimate solution for more difficult applications. They facilitate installation and maintenance even in tighter spaces.

MAXIMUM VERSATILITY
SERVICING THE INSTALLER.

- Brass head
- Rotational female brass unit with rotating nuts (DOSAPLUS 1 TA)
- Rotational female brass unit (DOSAPLUS 21 TA)
- Adjustment screw for correct dosing
- 2 pieces (head, cup)

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head: CW 602 N brass.
 Bowl: SAN.
 O-ring: EPDM.
 Breather-valve: body stainless steel, o-ring EPDM.
 Bellow: rubber (NBR).
 IN/OUT threads: CW 614 N brass, 1/2" BSP



21 TA 2P FF



1 TA 2P DG

ACCESSORIES INCLUDED	REFILL INCLUDED	WORKING CONDITIONS
 		Max working pressure _____ 8 bar (116 psi) Max working temperature _____ 45°C (113°F) Min working temperature _____ 4°C (39,2°F) Max total hardness _____ 35°f (350 ppm CaCO ₃)
spanner for Dosaplus 3P spanner for Dosaplus 2P	2 Poliphos A charge for Dosaplus	Remark - the treated water can be heated up to 75°C - 80°C, above that temperature the polyphosphate loses gradually its effectiveness.

